

➤ **Klebstoff-Film Performance**

sehr stark/sehr stark haftend

SPRINTIS Schenk GmbH & Co. KG
 Ludwig-Weis-Str. 11 · D-97082 Würzburg
 Tel. +49(0) 931 / 40 41 6-240 · Fax: -100

www.sprintis.de · info@sprintis.de

12/2023

Anwendungsbeispiele

Gut geeignet für Kunsthandwerk, Papierindustrie und verschiedene andere industrielle Anwendungen. Ausgezeichnete Haftung auf verschiedenen Arten von Oberflächen (Papier, Karton, Stoff, Leder, Metall, Holz, laminiert).

Eigenschaften

Kleberart	Acrylat
Trägermaterial	Ohne
Dicke (Kleber)	0,075 mm
Klebekraft	24 N/25mm (PSTC 101)
Abdeckung Material	Silikonpapier
Abdeckung Farbe	Braun
Temperaturbereich von/bis	130 °C
Lebensmittelkontakt	Nicht geeignet

Lagerempfehlung / Lagerzeit

Bei üblichen Lagerbedingungen bei Raumklima (ca. 50% relative Luftfeuchte & ca. 20 °C Raumtemperatur) besitzt das Produkt in Originalverpackung eine Lagerzeit von mindestens 12 Monaten nach Eingang beim Kunden.

Hinweis:

Die technischen Angaben geben wir Ihnen nach bestem Wissen, jedoch unverbindlich. Aufgrund der vielfältigen material- und umgebungsbedingten Einflüsse empfehlen wir vor jedem Gebrauch eine Eignungsprüfung an Originalmaterialien. Bitte beachten Sie dabei auch die für die Haftklebebänder üblichen Verarbeitungsbedingungen.

Adhesive film Performance

very strong/ very strong

SPRINTIS Schenk GmbH & Co. KG
Ludwig-Weis-Str. 11 · D-97082 Würzburg
Tel. +49 (0) 931 / 40 41 6-240 · Fax: -100

www.sprintis.eu · info@sprintis.eu

12/2023

Applications & purposes

Thick film of adhesive without backing, general purpose, to fix various items in industry, craft industry, at school and at home. High adhesion on all substrates (cardboard, paper, leather, fabrics, plastics, wood). Good ageing resistance.

Characteristics

Adhesive type	acrylic
Carrier material	without
Thickness (adhesive)	0.075 mm
Peel adhesion, adhesive strength	24 N/25mm (PSTC 101)
Release liner material	silicone paper
Release liner colour	brown
Temperature from/to	130 °C
Food contact	not suitable

Storage recommendation / Shelf life

Under normal storage conditions in a room climate (approx. 50% relative humidity & approx. 20 °C room temperature) the product in its original packaging has a storage period of at least 12 months after receipt by the customer.

Disclaimer:

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third part. We cannot assume any liability for the use of our products in conjunction with other materials.